

ガラス管ヒューズ  
Glass Tube Fuses (Normal-blow)

型名 FM, FR  
Type

電気特性

Electrical Characteristics

通電容量 110%  
Current-Carrying Capacity 110%  
溶断時間 135% 1時間以内  
Blowing-Time 135% 1Hour Max  
200% 2分以内  
200% 2Minutes Max


適用規格

Recognized Standard

UL Listed (100mA ~ 630mA)  
UL Recognized (800mA ~ 6.3A)  
UL 248-14 File No. E46712

カタログ番号 Catalog No.	カタログ番号 Catalog No.	定格 Rating
FM-0100	FR-0100	250V 100mA
FM-0125	FR-0125	250V 125mA
FM-0160	FR-0160	250V 160mA
FM-0200	FR-0200	250V 200mA
FM-0250	FR-0250	250V 250mA
FM-0315	FR-0315	250V 315mA
FM-0400	FR-0400	250V 400mA
FM-0500	FR-0500	250V 500mA
FM-0630	FR-0630	250V 630mA
FM-0800	FR-0800	250V 800mA
FM-1000	FR-1000	250V 1A
FM-1250	FR-1250	125V 1.25A
FM-1600	FR-1600	125V 1.6A
FM-2000	FR-2000	125V 2A
FM-2500	FR-2500	125V 2.5A
FM-3150	FR-3150	125V 3.15A
FM-4000	FR-4000	125V 4A
FM-5000	FR-5000	125V 5A
FM-6300	FR-6300	125V 6.3A

FM



4.6 × 14.5mm

FR



4.6 × 14.5mm  
リード線 Lead Wire  
0.6 × 32mm