

型名 MF61NM MF62NM  
Type


電気特性  
Electrical Characteristics

通電容量 110%  
Current-Carrying Capacity 110%  
溶断時間 135% 1時間以内  
Blowing-Time 135% 1Hour Max  
200% 2分以内  
200% 2Minutes Max

適用規格  
Recognized Standard


◆ 電気用品安全法(1 ~ 20A)  
METI Type(1 ~ 20A)

MF61NM



6.35 × 31.8mm

MF62NM



6.35 × 31.8mm

リード線 Lead Wire

0.8 × 35mm : 315mA ~ 8A  
1.0 × 35mm : 10A ~ 15A  
1.2 × 35mm : 20A

カタログ番号 Catalog No.	カタログ番号 Catalog No.	定格 Rating
MF61NM 250V 0.1	MF62NM 250V 0.1	250V 0.1A
MF61NM 250V 0.125	MF62NM 250V 0.125	250V 0.125A
MF61NM 250V 0.16	MF62NM 250V 0.16	250V 0.16A
MF61NM 250V 0.2	MF62NM 250V 0.2	250V 0.2A
MF61NM 250V 0.25	MF62NM 250V 0.25	250V 0.25A
MF61NM 250V 0.315	MF62NM 250V 0.315	250V 0.315A
MF61NM 250V 0.4	MF62NM 250V 0.4	250V 0.4A
MF61NM 250V 0.5	MF62NM 250V 0.5	250V 0.5A
MF61NM 250V 0.63	MF62NM 250V 0.63	250V 0.63A
MF61NM 250V 0.8	MF62NM 250V 0.8	250V 0.8A
MF61NM 250V 1	MF62NM 250V 1	250V 1A
MF61NM 250V 1.25	MF62NM 250V 1.25	250V 1.25A
MF61NM 250V 1.6	MF62NM 250V 1.6	250V 1.6A
MF61NM 250V 2	MF62NM 250V 2	250V 2A
MF61NM 250V 2.5	MF62NM 250V 2.5	250V 2.5A
MF61NM 250V 3.15	MF62NM 250V 3.15	250V 3.15A
MF61NM 250V 4	MF62NM 250V 4	250V 4A
MF61NM 250V 5	MF62NM 250V 5	250V 5A
MF61NM 250V 6.3	MF62NM 250V 6.3	250V 6.3A
MF61NM 250V 8	MF62NM 250V 8	250V 8A
MF61NM 250V 10	MF62NM 250V 10	250V 10A
MF61NM 250V 15	MF62NM 250V 15	250V 15A
MF61NM 250V 20	MF62NM 250V 20	250V 20A