

耐サージ型ヒューズ

Withstand Surge Current Type Fuses (Semi Time-Lag)

型名 **SB, SBR**
Type

電気特性

Electrical Characteristics

通電容量 110%
Current-Carrying Capacity 110%
溶断時間 135% 1時間以内
Blowing-Time 135% 1Hour Max
200% 2分以内
200% 2Minutes Max

カタログ番号 Catalog No.	カタログ番号 Catalog No.	定格 Rating
SB 250V 500	SBR 250V 500	250V 500mA
SB 250V 630	SBR 250V 630	250V 630mA
SB 250V 800	SBR 250V 800	250V 800mA
SB 250V 1	SBR 250V 1	250V 1A
SB 125V 1.25	SBR 125V 1.25	125V 1.25A
SB 125V 1.6	SBR 125V 1.6	125V 1.6A
SB 125V 2	SBR 125V 2	125V 2A
SB 125V 2.5	SBR 125V 2.5	125V 2.5A
SB 125V 3.15	SBR 125V 3.15	125V 3.15A
SB 125V 4	SBR 125V 4	125V 4A
SB 125V 5	SBR 125V 5	125V 5A
SB 125V 6.3	SBR 125V 6.3	125V 6.3A
SB 125V 8	SBR 125V 8	125V 8A
SB 125V 10	SBR 125V 10	125V 10A

適用規格

Recognized Standard

◆ 電気用品安全法(1~10A)
METI Type(1~10A)

UL UL Listed (500mA~10A)
UL 248-14 File No. E46712


CSA CSA Certified (500mA~10A)
CSA-C22.2 No.248-14 File No.LR36410

SB



φ 5.2 × 20mm

SBR



φ 5.2 × 20mm
リード線 Lead Wire
φ 0.8 × 35mm 500mA~8A
φ 1.0 × 35mm:10A